

PA-220

Palo Alto Networks PA-220 brings next-generation firewall capabilities to distributed enterprise branch offices, retail locations, and midsize businesses.

Key Security and Connectivity Features

Classifies all applications, on all ports, all the time

- Identifies the application, regardless of port, SSL/SSH encryption, or evasive technique employed.
- Uses the application, not the port, as the basis for all your safe enablement policy decisions: allow, deny, schedule, inspect, and apply traffic-shaping.
- Categorizes unidentified applications for policy control, threat forensics, or App-ID™ technology development.

Enforces security policies for any user, at any location

- Deploys consistent policies to local and remote users running on the Windows®, macOS®, Linux, Android®, or Apple iOS platforms.
- Enables agentless integration with Microsoft Active Directory® and Terminal Services, LDAP, Novell eDirectory™, and Citrix.
- Easily integrates your firewall policies with 802.1X wireless, proxies, network access control, and any other source of user identity information.

Prevents known and unknown threats

- Blocks a range of known threats—including exploits, malware and spyware—across all ports, regardless of common evasion tactics employed.
- Limits the unauthorized transfer of files and sensitive data, and safely enables non-work-related web surfing.
- Identifies unknown malware, analyzes it based on hundreds of malicious behaviors, and then automatically creates and delivers protection.

Enables SD-WAN functionality

- Easily adopt SD-WAN by simply enabling it on your existing firewalls.
- Enables you to safely implement SD-WAN, which is natively integrated with our industry-leading security.
- Delivers an exceptional end user experience by minimizing latency, jitter, and packet loss.



PA-220

The controlling element of the PA-220 is PAN-OS®, which natively classifies all traffic, inclusive of applications, threats, and content, and then ties that traffic to the user regardless of location or device type. The application, content, and user—in other words, the elements that run your business—then serve as the basis of your security policies, resulting in improved security posture and reduced incident response time.

Highlights

- High availability with active/active and active/passive modes
- Redundant power input for increased reliability
- Fanless design
- Simplified deployments of large numbers of firewalls through USB

Table 1: PA-220 Performance and Capacities

Firewall throughput (HTTP/appmix) ¹	500/580 Mbps
Threat Prevention throughput (HTTP/appmix) ²	240/280 Mbps
IPsec VPN throughput ³	500 Mbps
Max sessions	64,000
New sessions per second ⁴	4,200

1. Firewall throughput is measured with App-ID and logging enabled, using 64 KB HTTP/appmix transactions.

2. Threat Prevention throughput is measured with App-ID, IPS, antivirus, anti-spyware, WildFire, file blocking, and logging enabled, utilizing 64 KB HTTP/appmix transactions.

3. IPsec VPN throughput is measured with 64 KB HTTP transactions and logging enabled.

4. New sessions per second is measured with application-override utilizing 1 byte HTTP transactions.

The PA-220 supports a wide range of networking features that enable you to more easily integrate our security features into your existing network.

Table 2: PA-220 Networking Features
Interface Modes
L2, L3, tap, virtual wire (transparent mode)
Routing
OSPFv2/v3 with graceful restart, BGP with graceful restart, RIP, static routing
Policy-based forwarding
Point-to-Point Protocol over Ethernet (PPPoE)
Multicast: PIM-SM, PIM-SSM, IGMP v1, v2, and v3
SD-WAN
Path quality measurement (jitter, packet loss, latency)
Initial path selection (PBF)
Dynamic path change
IPv6
L2, L3, tap, virtual wire (transparent mode)
Features: App-ID, User-ID, Content-ID, WildFire, and SSL Decryption SLAAC
IPsec VPN
Key exchange: manual key, IKEv1, and IKEv2 (pre-shared key, certificate-based authentication)
Encryption: 3DES, AES (128-bit, 192-bit, 256-bit)
Authentication: MD5, SHA-1, SHA-256, SHA-384, SHA-512
VLANs
802.1Q VLAN tags per device/per interface: 4,094/4,094
Network Address Translation
NAT modes (IPv4): static IP, dynamic IP, dynamic IP and port (port address translation)
NAT64, NPTv6
Additional NAT features: dynamic IP reservation, tunable dynamic IP and port oversubscription
High Availability
Modes: active/active, active/passive
Failure detection: path monitoring, interface monitoring

Table 3: PA-220 Hardware Specifications
I/O
(8) 10/100/1000
Management I/O
(1) 10/100/1000 out-of-band management port
(1) RJ-45 console port
(1) USB port
(1) Micro USB console port
Storage Capacity
32 GB eMMC
Power Supply (Avg/Max Power Consumption)
Optional: dual redundant 40 W (21 W / 25 W)
Max BTU/hr
102
Input Voltage (Input Frequency)
100–240 VAC (50–60Hz)
Max Current Consumption
Firewall: 1.75 A @ 12 VDC
Power supply (AC side): 0.5 A @ 100 VAC, 0.2 A @ 240 VAC
Dimensions
1.62" H x 6.29" D x 8.07" W
Weight (Stand-Alone Device/As Shipped)
3.0 lbs / 5.4 lbs
Safety
cCSAus, CB
EMI
FCC Class B, CE Class B, VCCI Class B
Certifications
See https://www.paloaltonetworks.com/company/certifications.html
Environment
Operating temperature: 32° to 104° F, 0° to 40° C
Non-operating temperature: -4° to 158° F, -20° to 70° C
Passive cooling

To learn more about the features and associated capacities of the PA-220, please visit www.paloaltonetworks.com/products.



3000 Tannery Way
 Santa Clara, CA 95054
 Main: +1.408.753.4000
 Sales: +1.866.320.4788
 Support: +1.866.898.9087
www.paloaltonetworks.com

© 2019 Palo Alto Networks, Inc. Palo Alto Networks is a registered trademark of Palo Alto Networks. A list of our trademarks can be found at <https://www.paloaltonetworks.com/company/trademarks.html>. All other marks mentioned herein may be trademarks of their respective companies. pa-220-ds-112619